

AG

Side-shift rotary tiller

HP 15-30 KW 11-22

More information / Download PDF



(https://www.celli.it/wp-content/uploads/2008/11/ AG-attacco-inf-Goldoni-800x600.jpg)



An important feature of side shift rotary tillers is that they till soil both from the center and the sides with respect to the centerline of the tractor. This allows operation in areas that the tractor cannot reach due to its height (for example, under trees or near greenhouse walls). The gearbox always remains in the center so that the drive shaft always operates in a straight position, while the whole machine body shifts sideways.

Technical specifications and standard equipment

(https://www.celli • side-shift: manual it/en/)
• PTO: 1-Speed for 540 rpm: 205 rpm

- side transmission: chain
- c-shaped blades: 60×6 mm (4 for each flange, with the side blades leaning outwards)
- max. working depth 15 cm
- resting foot
- drive shaft without safety device
- · removable safety devices

Optional accessories

- Rotor with 6 blades per flange
- Double flange (2 pcs. each flange)
- Side-shift with threaded bar
- Pair of front wheels
- Extended upper and lower 3-point hitch fixed
- Extended upper and lower 3-point hitch removable
- Drive shaft with shear bolt
- Drive shaft with clutch

Ideal for:

- · Working with small tractors
- Tillling soil in orchards and vineyards
- Preparing seedbeds
- · Eliminating soil compacting
- Burying abundant crop residue
- Getting the right degree of soil finishing according to specific needs
- Carrying equipment on the roads without risks

Symbol key (https://www.celli.it/en/symbol-key/)

| AG | | | 2 7 2 | ₽2 | Δ <u>*</u> Δ | L | |
|-----|---------|-----|---------------------|---------|--------------|-----|--|
| | cm | cm | cm - cm | HP / KW | Kg | Nr. | |
| 85 | 100 | 85 | 42 - 43 17 - 68 | 15/11 | 155 | 16 | |
| 105 | 120 | 105 | 52 - 53 17 - 88 | 20/15 | 165 | 20 | Cardano S.4 L=832 lato trattore 1"3/8 Z=6 |
| 125 | 140 | 125 | 62 - 63 17 - 108 | 25/18 | 185 | 24 | |
| 145 | 160 | 145 | 72 - 73 17 - 128 | 25/18 | 205 | 28 | |