



(<https://www.celli.it/en/>)

BA

Side-shift rotary tiller

HP 20-40 KW 15-29

[More information / Download PDF](#)



(<https://www.celli.it/wp-content/uploads/2008/11/BA-rear-roller.jpg>)



An important feature of side shift rotary tillers is that they till soil both from the center and the sides with respect to the centerline of the tractor. This allows operation in areas that the tractor cannot reach due to its height (for example, under trees or near greenhouse walls). The gearbox always remains in the center so that the drive shaft always operates in a straight position, while the whole machine body shifts sideways.

Technical specifications and standard equipment



- maximum horsepower: 40 HP (29 KW)
(<https://www.celli.it/en/>)
- side-shift: manual
- PTO: 1-Speed for 540 rpm: 220 rpm with RH side rotation
- side transmission: chain
- L-shaped blades: 60×6 mm (6 for each flange, with the side blades leaning outwards)
- max. working depth 18 cm
- resting foot
- drive shaft without safety device
- removable safety devices









Optional accessories

- 1-speed gearbox with LH side rotation
- C-shaped blades
- Side blades leaning inwards
- Double flange (2 pcs. each flange)
- Side-shift with threaded bar
- Pair of front wheels
- Extended upper and lower 3-point hitch – fixed
- Extended upper and lower 3-point hitch – removable
- Drive shaft with shear bolt
- Drive shaft with clutch

Ideal for:

- Working with small tractors
- Cultivating around trees in vineyards and orchards
- Preparing seedbeds
- Eliminating soil compacting
- Burying abundant crop residue
- Getting the right degree of soil finishing according to specific needs
- Carrying equipment on the roads without risks

Symbol key (<https://www.celli.it/en/symbol-key/>)

 (https://www.celli.it/en/)							
	cm	cm	cm - cm	HP / KW	Kg	Nr.	
125	140	125	62 - 63 22 - 103	25/18	230	36	Cardano S.6 L=947 lato trattore 1"3/8 Z=6
145	160	145	72 - 73 22 - 123	30/22	245	42	
165	180	165	82 - 83 22 - 143	35/26	260	48	

Previous

« AG (<https://www.celli.it/en/products/rotary-tillers/side-shift-rotary-tillers/ag/>)

Next

S/BA » (<https://www.celli.it/en/products/rotary-tillers/side-shift-rotary-tillers/s-ba/>)

Request for information

Fill out the form to ask for information on the product pages

Information request

First Name *

Last Name *

Email *

Company *

Telephone *

Address *

City *

State/Province *