



(<https://www.celli.it/en/>)

DERBY

Side-shift rotary tiller

HP 35-60 KW 26-44


[More information / Download PDF](#)



This new side shift rotary tiller, suitable for tractors with up to 60 HP of power, has been designed paying much attention to the lateral displacement system, which is based on a sturdy central attachment that shifts on two chrome sliding shafts and is activated (manually) using a screw. In the decentralized position, this machine can easily reach terrain beneath low trees and vegetation, where the tractor cannot operate due to its height limitations. Other technical machine features include those typical of Celli products: category I and II 3-point hitch, sturdy box frame structure, wide rear fan for perfect leveling, thoroughly tested transmission components, including lateral transmission with gears.

Technical specifications and standard equipment

- maximum horsepower: 60 HP (44 KW)
- side-shift: manual
- PTO: 1-Speed for 540 rpm: 235 rpm
- gear side transmission
- L-shaped blades: 70×7 mm (6 blades each flange, side blades leaning inwards)
- max. working depth 20 cm


 • resting foot
 • skids
 • power shaft with clutch
 • removable safety devices








Optional accessories

- C-shaped blades
- Side blades leaning outwards
- Double flange (2 pcs. each flange)
- Hydraulic side-shift kit

Ideal for:

- Working with small tractors
- Cultivating around trees in vineyards and orchards
- Tillage soil in orchards and vineyards
- Preparing seedbeds
- Eliminating soil compacting
- Burying abundant crop residue
- Getting the right degree of soil finishing according to specific needs
- Carrying equipment on the roads without risks

Symbol key (<https://www.celli.it/en/symbol-key/>)

DERBY							
	cm	cm	cm - cm	HP / KW	Kg	Nr.	
155	175	160	80 - 80 21 - 139	40/29	435	36	Cardano S.5 L=918 lato trattore 1"3/8 Z=6
180	200	185	92 - 93 21 - 164	50/37	470	42	
205	225	210	105 - 105 21 - 189	50/37	495	48	

Previous

« S/BA (<https://www.celli.it/en/products/rotary-tillers/side-shift-rotary-tillers/s-ba/>)

Next

BV-BF-BFF » (<https://www.celli.it/en/products/rotary-tillers/side-shift-rotary-tillers/bv-bf-bff/>)