



(<https://www.celli.it/en/>)

S/BA

Side-shift rotary tiller

HP 20-40 KW 15-29

[More information / Download PDF](#)



(<https://www.celli.it/wp-content/uploads/2008/11/SBA-1-800x600.jpg>)



(<https://www.celli.it/wp-content/uploads/2008/11/SBA-additional-reservoir.jpg>)



The S/BA hydraulic side shift rotary tiller completes the already extensive Celli range of soil processing machines for vineyards and orchards. The S/BA is the best choice for those who do not need an automatic side shift rotary tiller (such as the H/BA model) but do need a simple and reliable machine that adapts easily to various working conditions, thanks to hydraulic adjustment of side shifting, which can be activated manually from the tractor. The S/BA maintains all the basic technical features of the most expensive H/BA rotary tiller!

Technical specifications and standard equipment



- maximum horsepower: 40 HP (29 KW)
- side-shift: hydraulic manual
- PTO: 1-Speed for 540 rpm: 221 rpm
- side transmission: chain
- c-shaped blades: 60×6 mm (6 blades each flange, side blades leaning inwards)
- max. working depth 18 cm
- front skids
- drive shaft without safety device

Optional accessories

- Double flange (2 pcs. each flange)
- Pair of front wheels
- Drive shaft with shear bolt
- Drive shaft with clutch

Ideal for:

- Working with small tractors
- Cultivating around trees in vineyards and orchards
- Tillage soil in orchards and vineyards
- Preparing seedbeds
- Eliminating soil compacting
- Burying abundant crop residue
- Getting the right degree of soil finishing according to specific needs
- Carrying equipment on the roads without risks

Symbol key (<https://www.celli.it/en/symbol-key/>)

S/BA							
	cm	cm	cm - cm	HP / KW	Kg	Nr.	
125V	137	125	58 - 67 28 - 97	25/18	250	36	Cardano S.6 L=947 lato trattore 1"3/8 Z=6
145V	157	145	68 - 77 38 - 107	30/22	280	42	
165V	177	165	78 - 87 48 - 117	35/26	310	48	
125F	137	125	48 - 77 18 - 107	25/18	250	36	
145F	157	145	48 - 97 18 - 127	30/22	280	42	
165F	177	165	48 - 117 18 - 147	35/26	310	48	