



(<https://www.celli.it/en/>)

# TIGER 280DDF (T280DDF)

## Dual-drive fixed Frangor

HP 180-280 KW 132-206

[More information / Download PDF](#)



The Frangor version is recommended for seedbed preparation when thorough soil refinement is required. It is different from the rotary tiller version due to the following modifications:

- toothed rotor or straight tines for accurate soil finishing.
- the rotor rotates faster than the rotary tiller
- rear swinging articulated tailgate (rear fan) that offers a wide range of adjustment positions
- rear leveling roller (available in cage, spikes and packer models).

## Technical specifications and standard equipment

- maximum horsepower: 280 HP (206 KW)
- PTO: 2-speed gearbox for 1000 rpm, No. of teeth: 18-27 = 340 rpm – 19-26 = 375 rpm
- gear side transmission
- Cat. 2 and 3 3-point hitch
- swinging front hitches
- rear tailgate adjustment by threaded bar
- leveling rollers, adjustment by hydraulic rams

- teeth: 30×30 mm L=170 mm
- max. working depth 20 cm
- (https://www.celli.it/en/level-drive) shafts with snap safety device
- on central drive shaft
- removable safety devices

## Optional accessories

- Gearbox 360 HP
- Pair of front wheels, adjustable with hydraulic rams
- Pair of front sod breaking discs
- Quick roller release
- Front track eraser
- Hydraulic kit for tailgate adjustment

## Ideal for:

- Working with tractors above 190 HP
- Cultivating heavy and sticky soil
- Working in rocky soil
- Working soil in depth
- Preparing large fields quickly
- Breaking up the hardest soil
- Eliminating soil compacting

Symbol key (<https://www.celli.it/en/symbol-key/>)

TIGER280DDF (T280DDF)										
	cm	cm	HP / KW	Kg	Kg	Kg	Kg	Nr.	Nr.	
400	413	391	180/132	2400	2400	2667	2540	70 + 6*	112 + 4*	Cardano S.10 L=834 lato trattore 1"3/8 Z=21
450	463	441	200/147	2544	2544	2827	2692	80 + 6*	128 + 4*	
500	513	491	220/162	2688	2688	3016	2845	90 + 6*	144 + 4*	

TIGER 280DDF (T280DDF)				
	Ø	Ø	Ø	Ø
400	500	560	555	470
450				
500				

\* **L-shaped inner blades**