



(<https://www.celli.it/en/>)

ENERGY

Fixed power harrow

HP 80-200 KW 59-146

[More information / Download PDF](#)



(<https://www.celli.it/wp-content/uploads/2008/11/energy-2.jpg>)



(<https://www.celli.it/wp-content/uploads/2008/11/Energy-P-10-op.jpg>)



(https://www.celli.it/wp-content/uploads/2008/11/Energy_gearbed_section.jpg)



(<https://www.celli.it/wp-content/uploads/2008/11/Energy-P-30-op.jpg>)



Technical specifications and standard equipment

- maximum horsepower: 200 HP (146 KW)
- PTO: 1000 rpm with 2-speed gearbox No. of teeth for mod. 250-350: 25-14 = 323 rpm; 24-15 = 360 rpm No. of teeth for mod. 300-400: 14-25 = 323 rpm; 15-24 = 360 rpm



- Cat. 2 3-point hitch
- Hanging front hitches
- (https://www.celli.it/en/energy/roller-adjustment-by-pins) roller adjustment by pins
- (https://www.celli.it/en/energy/leveling-bar-adjustment-with-threaded-bar) rear leveling bar adjustment with threaded bar
- tines 120x15x300 mm: working depth about 30 cm
- mobile side plates
- drive shaft with shear bolt
- removable safety devices

Optional accessories











- 4-speed gearbox for 540 rpm PTO mod. 250-350 No. of teeth 21-18 = 267 rpm; 20-19 = 296 rpm No. of teeth 19-20 = 328 rpm; 18-21 = 363 rpm mod. 300-400 No. of teeth 18-21 = 267 rpm; 19-20 = 296 rpm No. of teeth 20-19 = 328 rpm; 21-18 = 363 rpm
- 2-speed gearbox with rear PTO for 1000 rpm*
- 4-speed gearbox with rear PTO for 540 rpm*
- Counterplate for tine locking (rotor kit)
- Gearbox oil cooling kit
- Rear rollers
- Hydraulic kit for roller adjustment
- Stone protector kit for rotor
- Quick tine fitting kit
- Front track eraser
- Rear hydraulic hitches for seeder
- Drive shaft with clutch safety device
- Drive shaft with automatic safety device (\geq model 350)





**NOTE: When the machine is equipped with rear PTO, the oil cooling kit cannot be fitted (and vice versa).*

Ideal for:

- Working with large tractors
- Working with tractors above 190 HP
- Cultivating heavy and sticky soil
- Working in rocky soil
- Working soil in depth
- Preparing large fields quickly
- Preparing seedbeds
- Eliminating soil compacting
- Getting the right degree of soil finishing according to specific needs

Symbol key (<https://www.celli.it/en/symbol-key/>)

									
(https://www.celli.it/en/)	cm	cm	HP / KW	Kg	Kg	Kg	Kg	Nr.	
250	255	250	80/59	1050	1050	1200	1080	20	Cardano S.8 L=893 lato trattore 1"3/8 Z=21
300	305	300	100/73	1170	1170	1340	1200	24	
350	355	350	130/95	1290	1290	1480	1320	28	Cardano S.10 L=896 lato trattore 1"3/8 Z=21
400	405	400	150/109	1410	1410	1620	1440	32	

ENERGY				
	Ø	Ø	Ø	Ø
250	440	560	470	470
300				
350				
400				

Previous

« RANGER/S (<https://www.celli.it/en/products/power-harrows/fixed-power-harrows/ranger-s/>)

Next

MAXI » (<https://www.celli.it/en/products/power-harrows/fixed-power-harrows/maxi/>)

Request for information

Fill out the form to ask for information on the product pages

Information request

First Name *

Last Name *

Email *

Company *