



(<https://www.celli.it/en/>)

AB

Stone Burier

HP 20-40 KW 15-29

Contact us for more information



NOTE: Cylindrical roller optional

For garden applications

Technical specifications and standard equipment

- maximum horsepower: 40 HP (29 KW)
- side-shift: manual
- PTO: 1-Speed for 540 rpm: 220 rpm with LH side rotation
- side transmission: chain
- L-shaped blades: 60×6 mm (6 for each flange, with the side blades leaning outwards)
- max. working depth 18 cm
- resting foot
- drive shaft with bolt
- removable safety devices
- mesh roller

Optional accessories










- Cylindrical roller
(<https://www.celli.it/en/>)
- Double flange (2 pcs. each flange)

Ideal for:

- Working with small tractors
- Working in rocky soil
- Tillling soil in orchards and vineyards
- Preparing seedbeds
- Breaking up the hardest soil
- Eliminating soil compacting
- Burying abundant crop residue
- Getting the right degree of soil finishing according to specific needs
- Carrying equipment on the roads without risks

Symbol key (<https://www.celli.it/en/symbol-key/>)

AB							
	cm	cm	cm - cm	HP / KW	Kg	Nr.	
95	110	95	47 - 48 22 - 73	20/15	294	30	Cardano S.5 L=837 lato trattore 1"3/8 Z=6
105	120	105	52 - 53 22 - 83	20/15	300	30	
125	140	125	62 - 63 22 - 103	25/18	306	36	
145	160	145	72 - 73 22 - 123	30/22	330	42	

Previous

« Fixed stone buriers (<https://www.celli.it/en/products/stone-buriers-and-bed-formers/fixed-stone-buriers/>)

Next

ARES » (<https://www.celli.it/en/products/stone-buriers-and-bed-formers/fixed-stone-buriers/ares/>)

Request for information