



Mulcher with reversible hydraulic feeder, ideal for pruning of olive trees, citrus trees and nuts.

Adapted to crush residues from 6-8 cm of diameter, with the rotor ÓCLAME of SERRAT which is adapted for tractors between 70 and 110 HP.

It works in reverse to preserve the tractor for doesn't pass at the top of the branches.

CHARACTERISTICS

- Steel-plate chassis, thickness 8 mm.
- Rotor ÓCLAME of 450 mm of diameter.
- Gearbox SERRAT.
- Side belt transmission 3 XPC.
- Treated knives.
- Supports of bearing rotor in Steel.
- Oscillating bearings of double row of rollers.
- Double bearing on rear roller.
- PTO 1.000 rpm.
- Triple feed chain.
- High torque hydraulic motor reversible.
- Hydraulic feeder, system BRALAKC.
- Model built under EC Normative.
- Safety indicators visible to personnel.



Feeder Bralake



Rotor Óclame Technology



MODEL	mm	KW-HP	kg	Nº BELTS TYPE	Diagram Dimensions							
					A mm	A in	B mm	B in	C mm	C in		
T-1600	1650	52 - 70 82 - 110	66	1100	3 XPC	2210	87"	1750	69"	1240	49"	1000
T-1800	1800	52 - 70 82 - 110	78	1230	3 XPC	2360	92"	1750	69"	1240	49"	1000

OPTIONS

- Freewheel on sleeve



- Steering Wheels

