

# serrat

## INTERPIQUET



Mechanical driven swing arm mower can be used to mow around trees, posts, crash barrier, etc. Without any damage.

Mechanical transmission by power take-off for tractors between 35 and 105 hp.

Requiring a double effect hydraulic's service for the slope and a simple effect service for the hydropneumatic suspension.

### CHARACTERISTICS

- 3 point hitch - cat. 2.
- Cutting width of 800 mm (32 inches) and 1.200 mm (47 inches).
- Backwardation from the axis of the tractor of 2.000 mm (79 inches) and 3.100 mm (122 inches).
- Length for the transport of 2.300 mm (90 inches) and 3.000 mm (118 inches).
- PTO 540 rpm.
- Mechanical transmission by power take-off.
- Pushing control by hydropneumatic suspension (adjustable).
- Hydraulic recovery control (adjustable).
- Hydraulic location according to the necessity activated from the tractor (1 double effect's service).
- 3 retractable knives.
- Lower bowl of control on the ground and rear wheel.
- Model built under the new 2006/42/CE Normative.
- Safety indications visible by the staff.



# serrat

Pushing control by hydropneumatic suspension (adjustable).  
Hydraulic recovery control (adjustable).



Control wheel of height of work.



MODEL												
	mm	KW-HP				A mm	A in	B mm	B in	C mm	C in	
INTERPIQUET	3100	26 - 35 77 - 105	3	285		3000	118"	3100	122"	1200	47"	540

### OPTIONS

- DIR
- Protection
- Rubber sleeve around the plate.



# serrat

Carretera nacional 240 km. 149,3  
22310 Castejón del Puente (Huesca)-España  
Tfno. (+34) 974 417 830  
Fax. (+34) 974 410 059  
[www.serrat.com](http://www.serrat.com) - [comercial@serrat.es](mailto:comercial@serrat.es)

